

**DECLARATION OF PERFORMANCE  
No 1071-CPD-1222**

1. Unique identification code of the product-type:  
**Celit 3D & 4D**
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:  
**SB.HLS**
3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:  
**Wood-based panels for use in construction**
4. Name and contact address of the manufacturer as required under Article 11(5):  
**Hunton Fiber AS  
Po Box 633  
NO-2810 GJOEVIK, Norway**
5. Where applicable, name and contact address of the authorized representative, specified in Article 12 (2):  
**Contact the manufacturer**
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:  
**System 2+**
7. In case of declaration of performance concerning a product covered by a harmonized standard  
**NS-EN 13986:2004 SINTEF Byggforsk  
EU-Notified Body No 1071**
8. Not applicable
- 9.

Essential characteristics	Performance	Harmonized technical specification
Thickness	+/- 1,2 mm	EN 13986:2004
Length/width	+/- 2 mm/m	EN 13986:2004
Squareness	< 2 mm/m	EN 13986:2004
Edge straightness	< 1,5 mm/m	EN 13986:2004
Thickness swelling	< 6 %	EN 13986:2004
Humidity content	6-12 %	EN 13986:2004
Thermal resistance 3D/4D	0,35 m <sup>2</sup> K/W/0,45 m <sup>2</sup> K/W	EN 13986:2004
Bending strength	≥ 1,2 N/mm <sup>2</sup>	EN 13986:2004
E-modulus in bending	= 140 N/mm <sup>2</sup>	EN 13986:2004
Moisture resistance	Sd = 86 mm (mean value)	EN 13986:2004

10. The performance of the product identified in 1 and 2 is in conformity with the performance in 9

Lars Harald Nilsen, QA & HES Mngr

GJOVIK 05.06.2013

Place/Date



**HUNTON FIBER AS**