

LBS 6,0

Multi roofing screw for use in light weight concrete (min. 600 kg / m³) or wooden decks

Required length:

Leight weight concrete: build up + 60 mm

Wood: build up + 20 mm

Note: pull-out test recommended

Approvals

- Sintef technical approval 2516
- ETA approval 08/0285



Material
Enduroguard coating
15 cycles

Screw
Torx-25 head
S-point
Without pre-drill

Length
From 60 to 240 mm

Products

PRODUCT CODE	Ø MM x LENGTH MM	PACKAGING
1413097	LBS-60060 6,0 X 60mm	1000/Bucket
1413098	LBS-60070 6,0 X 70mm	500/Bucket
1413099	LBS-60080 6,0 X 80mm	500/Bucket
1413101	LBS-60100 6,0 X 100mm	500/Bucket
1413103	LBS-60120 6,0 X 120mm	500/Bucket
1413105	LBS-60140 6,0 X 140mm	500/Bucket
1413106	LBS-60160 6,0 X 160mm	500/Bucket
1413107	LBS-60180 6,0 X 180mm	500/Bucket
1413108	LBS-60200 6,0 X 200mm	500/Bucket
1413109	LBS-60220 6,0 X 220mm	500/Bucket
1413110	LBS-62240 6,0 X 240mm	500/Bucket

Associated products



R 45 (FM approval)

Modified PP
Size: Ø 75 mm
Length: 20 t/m 730 mm



R 75 (FM approval)

Modified PP
Size: Ø 75 mm
Length: 20 t/m 330 mm



RBS 50

Modified PP
Size: Ø 50 mm
Design load values: 600 - 930
Newton