

# R 75 (FM APPROVAL)

## Standard tube for fastening of thermal insulation boards or base layer

From length 40 mm till 210 mm, this tube is also available in Large Nose (LN) edition, for the perfect combination with the LBS Ø 8,0 mm screw. ASTL for tapered insulation see Concrete deck.

### Approvals

- Sintef technical approval 2516
- ETA approval 08/0285
- FM approval ID-Nr.3034551



Size (diameter)  
Ø 75 mm

Material  
Modified Polypropylene

Length  
20 to 330 mm

## Products

PRODUCT CODE	Ø MM X LENGTH MM	PACKAGING
1412495	R75-020, 75 X 20mm	1000
1412496	R75-040, 75 X 40mm	500
1412497	R75-060, 75 X 60mm	500
1412498	R75-080, 75 X 80mm	500
1412499	R75-090, 75 X 90mm	500
1412500	R75-100, 75 X 100mm	500
1412501	R75-120, 75 X 120mm	500
1412503	R75-150, 75 X 150mm	500
1412505	R75-180, 75 X 180mm	250
1412507	R75-210, 75 X 210mm	250
1412509	R75-240, 75 X 240mm	250
1412510	R75-270, 75 X 270mm	250
1412511	R75-300, 75 X 300mm	250
1412512	R75-330, 75 X 330mm	250

## Associated products



### **BS 4,8 (FM Approval)**

For use with BIT-T25  
Torx-25 head  
Ø 4,8 mm



### **CS 6,1 (FM Approval)**

Pre-drill: 5,0 mm.  
In hard concrete 5,2 mm  
Torx-25 head  
Hi-lo thread



### **LBS 6,0**

Torx-25 head  
S-point  
Length: 60 to 240 mm



### **PS 4,8**

For use with BIT-T25  
Torx-25 head  
Ø 4,8 mm