

## THREE PLY PANEL technical data

<b>Specie:</b>	<b>LARCH</b>
<b>Lenght:</b>	4000 - 5050 mm
<b>Width:</b>	2050 mm
<b>Thickness:</b>	19 und 27 mm
<b><u>CE-certificate:</u></b>	PH Dresden, according to EN 13986
<b>QUALITY</b>	<b>A/B</b> according to EN 13017-1
<b>A</b>	<b>A-face</b> almost clear, sound knots, little resin pockets.
<b>B</b>	<b>B - backface</b> inferior defects allowed, some discoloration, sound and replaced knots.
<b><u>Glueing:</u></b>	according to AW 100 DIN 68705 part 2, WBP Ö-NORM B 3022 - VF for exterior and interior applications.
<b><u>Structure:</u></b>	crosswise glued – 3-ply
<b><u>Faces:</u></b>	unjoined strips, same widths , glued joints.
<b><u>Middle layer:</u></b>	spruce – unjoined strips, glued joints
<b><u>Humidity:</u></b>	at factory about 8 %
<b><u>Surface:</u></b>	both faces sanded K80
<b><u>Packing:</u></b>	bundelwise wrapped in plastic foil, protected against humidity, light-edges protected.
<b><u>Marks:</u></b>	specie, quality, thickness, dimensions

Our timber originates from controlled forest-areas beying supervised by actual law.

*Technical modification without prior notice.*  
mhpl3laeen94